



MULTI-CONDUCTOR UNSHIELDED CL3R CABLES

Gauge Size	No. of Conductors	Stranding	Insulation Thickness	Jacket Thickness	Nominal O.D.
12	2	65	.012	.020	.276
14	4	19	.012	.018	.262
14	2	26	.012	.018	.224
16	4	26	.010	.015	.213
16	3	26	.010	.015	.194
16	2	26	.010	.015	.182
18	12	7	.009	.015	.294
18	10	7	.009	.015	.284
18	8	7	.009	.015	.241
18	6	7	.009	.015	.221
18	4	7	.009	.015	.184
18	3	7	.009	.015	.167
18	2	7	.009	.015	.157
20	12	7	.008	.015	.247
20	10	7	.008	.015	.239
20	8	7	.008	.015	.203
20	6	7	.008	.015	.187
20	4	7	.008	.015	.156
20	3	7	.008	.015	.143
20	2	7	.008	.015	.135
22	16	7	.008	.015	.241
22	12	7	.008	.015	.221
22	10	7	.008	.015	.214
22	8	7	.008	.015	.182
22	6	7	.008	.015	.168
22	5	7	.008	.015	.154
22	4	7	.008	.015	.141
22	3	7	.008	.015	.129
22	2	7	.008	.015	.122
24	4	7	.008	.015	.127
24	2	7	.008	.015	.110

Construction:

Stranded bare copper conductors insulated with color coded PVC, jacketed with Gray PVC. Cables are twisted prior to jacketing.

**(UL) Standard 13,444
NEC Article 725,800**



COLOR CODE: Black, Red, White, Green, Orange, Blue, Brown, Yellow, Purple, Gray, Pink, Tan, Light Green, Light Blue, Light Orange, Light Purple

Above cables are also available as pairs or triads; unshielded, overall shielded, each group shielded.